



DESCRIPTION

ARISTA PREMIUM Odorless Fixer is a rapid fixer without the odor of most fixers. It is suitable for use in small, closed areas with little ventilation and for use by persons with respiratory sensitivities. This non-corrosive formula can be used in both machine and manual processing of film and paper.

REPLENISHER RATES AND SPECIFICATIONS

The replenishment rate is based on the type of film or paper selected. The recommended starting rate is 0.30 to 0.50 mls of fixer replenisher per square inch of film and 0.15 mls per square inch of paper.

Working solution pH at 25°C (77°F) = 5.00

Sp. gr. at 25°C = 1.102

SUGGESTED OPERATING PARAMETERS

Dilution:

For films 1+4

For paper 1+9

Fixing times:

Films: Clearing time can be less than 20 seconds; but fix for double your clearing time.

Papers: Fixing can be less than 15 seconds.

Fixing for longer than 90 seconds will not yield superior results for either film or paper.

Use **ARISTA PREMIUM Odorless Stop Bath** to extend fixer capacity.

Temperature:

For tray processing, use at 65°F to 85°F.

In processors, the fixer can be used up to 105° F.

Hardener: Many papers and some films do not require hardener. The emulsions are hard enough to withstand handling and processing. If hardener is needed, use enough hardener to achieve the desired results.

Suggested usage, between 2 oz. to 4 oz. per working strength gallon.