Material Safety Data Sheet

PremierArt - Print Shield - Aerosol Can

For CHEMICAL EMERGENCY 24/7 CALL
INFOTRAC 1 - 800 - 535 – 5053
Outside the US, call collect 1- 352 – 323 - 3500

Section I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:	PremierArt Print Shield
General Use:	Spray varnish sealer for ink jet prints
Product Description:	Aerosol spray sealer
Manufactured For:	Premier Imaging Products, LTD.
	2245-I Renaissance Drive, Las Vegas, NV 89119
TELEPHONE No.:	1 - 805 - 983 - 1472

Section II - COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	% Wt.	CAS No.	EEC No.	Symbol	Risk	EXPOSURE LIMITS Long Term (8 Hours) ppm	Long Term (8 Hours) mg/m^3	Short Term (15 mins) ppm	Short Term (15 mins) mg/m^3
Isopropyl Alcohol	40-60	67-63-0	200-661-7	F	11, 36, 67	400	999	500	1250
Dimethyl Ether	40-60	115-10-6	204-065-8	F+	12	400	766	500	958
n-Butyl Acetate	1-3	123-86-4	204-658-1	F	10, 66, 67	150	742	200	966

Remaining ingredients not considered hazardous under EC/CHIP2 regulations

Section III - HAZARDS IDENTIFICATION

Extremely Flammable. Vapor harmful. The principal safety and health hazards when using the product are due to inhalation of isopropanol vapors. There is also a risk of ignition of the spray should it pass through or on an ignition source. Inhalation may occur while spraying the product or during the drying process. If the product is used with adequate ventilation, risk of excessive inhalation is eliminated.

Section IV - FIRST AID MEASURES

EYES : Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation persists.

SKIN : Wash with soap and water. Get medical attention if irritation or rash develops. Remove and launder contaminated clothing before reuse.

INGESTION: If fully conscious, drink plenty of water. Induce vomiting. Get medical attention.

INHALATION: Remove to fresh air. If not breathing, apply artificial respiration. Get immediate medical attention

ADVICE TO PHYSICIAN : Treat symptoms.

Section V - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam for alcohols, water fog/ spray.

FIRE/EXPLOSION HAZARDS: Containers are under pressure. Exposure to high heat may result in explosion.

FIRE FIGHTING MEASURES: Wear a self-contained breathing apparatus and full protective gear. Cool cans with water.

NFPA HAZARD CODES: Health/Flammability/Reactivity **2 4 1**

Section VI - ACCIDENTAL RELEASE MEASURES

Evacuate area. Provide adequate ventilation. Contain spill to a small area. Flush away from ignition sources with water. Pick up with absorbent material and transfer to suitable container for disposal. Keep out of sewers, streams and waterways.

Section VII - HANDLING AND STORAGE

Do not puncture or crush container, even when empty. Keep away from open flames and sparks.

Store above 0^{o}C (32^{o}F) and below 49^{o}C (120^{o}F). Do not store in direct sunlight.

Section VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels. Use a fume hood if PEL/TLV may be exceeded.

RESPIRATORY PROTECTION: Respiratory protection is recommended when exposure limit is exceeded. Wear an approved organic respirator.

PROTECTIVE GLOVES: Not normally required. Wear chemical resistant gloves, if skin contact may occur.

EYE PROTECTION: **Wear safety glasses or goggles**.

Section IX - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Clear low viscosity liquid with an alcohol odor.

BOILING POINT: 82.5°C (181°F) (Isopropanol)

FLASH POINT: 12°C (53°F) open cup (Product only)

AUTOIGNITION TEMP: not determined

VAPOUR PRESSURE: not determined

SOLUBILITY IN WATER: Miscible

FREEZING POINT: Less than 0°C

SPECIFIC GRAVITY: 0.78 kg/l

pH: Not applicable

VAPOUR DENSITY: >1 (Air = 1)

EVAPORATION RATE: <1 (Ether#1)

% VOLATILE (BY VOLUME): 90

FLAMMABLE LIMITS: Lower: 2.0 Upper: 12.7 (Isopropanol)

Section X - STABILITY AND REACTIVITY

STABLE: Yes

INCOMPATIBILITY: Strong Oxidizers, strong inorganic acids.

HAZARDOUS DECOMPOSITION PRODUCTS: May include oxides of carbon, nitrogen and other toxic fumes.

HAZARDOUS POLYMERISATION: Will not occur.

Section XI - TOXICOLOGICAL INFORMATION

PRIMARY ROUTE OF EXPOSURE: Inhalation, skin and eye contact

ACUTE EFFECTS:

EYES: Eye contact may cause irritation.

INHALATION: Inhalation in excess of PEL/TLV may result in dizziness and headache and in extreme cases, loss of consciousness.

SKIN: Repeated or prolonged skin contact may cause skin irritation.

CHRONIC EFFECTS: None expected from available data.

CANCER INFORMATION: This product contains no ingredient that is listed on the **IARC**, **NTP**, or **OSHA** carcinogen lists.

Section XII - ECOLOGICAL INFORMATION

No data available

Section XIII - DISPOSAL CONSIDERATIONS

Do not incinerate. Bury in licensed facility. Follow Federal, State, and local regulations.

Section XIV - TRANSPORTATION INFORMATION

TDG: Aerosol, 2.1, UN1950 **IMDG**: Aerosols, Class 3, UN1950, ERG No.12

IATA/CAO: Aerosols, Flammable, N.O.S., UN 1950

ARD/RID: Aerosol Dispensers, 2, 5°F ARD.UN1950

U.S. DOT: Consumer Commodity ORM-D for package weights more than 30 Kg. - Aerosols, Flammable, N.O.S., UN

Section XV - REGULATORY INFORMATION

EUROPEAN CLASSIFICATION: F+, Extremely flammable; R-Phrase - Extremely flammable; S-Phrase - keep away from ignition sources, no smoking.

CANADIAN CLASSIFICATION: B-2: Flammable aerosol; R-Phrase - Flammable; S-Phrases - keep away from sources of ignition, no smoking; Do not breathe spray; Use only in well ventilated areas.

Section XVI - OTHER INFORMATION

HMIS Rating : Health : 2 Flammability : 4 Reactivity : 1

CERCLA/SUPERFUND,40 CFR 302.4: Dimethyl Ether is reportable, 100 lbs (45.4 kg.).

TOXIC SUBSTANCES CONTROL ACT (TSCA) : The ingredients of this product are all on the TSCA inventory list.

SARA TITLE III, 313 CHEMICALS: None

CALIFORNIA PROPOSITION 65: This product contains no chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

This information is based solely on the data provided by the suppliers of the materials used and/or recognized technical sources, not on the mixture itself and is believed to be correct as of this date.

No warranty is expressed or implied regarding the accuracy of the data.